# NOVA FOAM PAD (FP) DOCK SEAL COMPETITIVE PRODUCT COMPARISON

### **FEATURES AND BENEFITS**

- Designed for door openings up to 9 x 9-feet
- High-density polyurethane compression foam head and side pads
- Standard pad projection is 10-inches
- · Pressure-treated, kiln-dried wood frame
- · Foam is chemically bonded to the frame
- Standard full-height yellow guide stripes
- · Heavy-duty galvanized mounting hardware
- Pads are vented for air and moisture release
- Top-grade fabrics provide superior performance and maximum durability
- Velcro® attachments
- · All sew lines are lock-stitched and reinforced with UV-resistant thread

**BUILT TO LAST:** All NOVA Dock Seal standard frames are made from pressure-treated and kilndried wood for greater moisture resistance and enhanced durability.

DOCK SEAL	PRESSURE-TREATED, KILN-DRIED WOOD FRAME			
NOVA FP	✓ YES			
Competitor 1	x NO			
Competitor 2	x NO			
Competitor 3	x NO			

FASTER, EASIER REPAIRS: Unlike competitors who fully wrap the wood backing, the FP Dock Seal is stitched along the sides for cleaner removal of cover fabrics, easier recovers and less dock downtime.





## MORE OPTIONS FOR SAFETY, DURABILITY

**AND STYLE:** The FP Series is available in six fabric selections and four different colors, many available with an optional flame-retardant design that selfextinguishes a flame in two seconds or less.

DOCK SEAL	FLAME-RETARDANT AND SELF- EXTINGUISHING OPTIONS			
NOVA FP	✓ YES			
Competitor 1	x NO			
Competitor 2	x NO			
Competitor 3	x NO			

# TESTED AND PROVEN TO PERFORM: NOVA's cover materials and fabrics have undergone rigorous testing and feature the highest puncture, tear and abrasion resistance in the industry.

FABRIC PROPERTIES & COLORS									
Fabric	Abrasion Resistance (cycles) Fed Std 5306 ASTM D3884	Tensile Strength (lbs./in.) Fed Std 5100 ASTM D751	Tear Strength (lbs., WxL) Fed Std 5134 ASTM D2261	Cold Resistance (at -40°F) Fed Std 5874 ASTM D2136	Colors				
NOVA MAX-1000™	65000	1000 x 1000	200 x 200	Pass					
NOVA MAX-60™	3000	950 x 850	160 x 130	Pass					
40 oz. NOVALON™	1500	400 x 350	50 x 50	Pass					
16 oz. NOVALON™	100	400 x 350	50 x 40	Pass					
40 oz. Vinyl	3000	950 x 850	160 x 130	Pass					
22 oz. Vinyl	1850	695 x 650	120 x 100	Pass					

