

NOVA GAP SEALER (GS) DOCK SHELTER

SURVEY

SITE SURVEY INFORMATION

Number of Doors _____

Door Width (W) _____ FT. _____ IN.
 Door Height (H) _____ FT. _____ IN.
 Dock Height (D) _____ IN.
 Bumper Projection (B) _____ IN.
 Wall Setback (S) _____ IN.
 Leveler Cantilever (C) _____ IN.
 Distance Between Doors _____ IN.


Projections for Typical Dock/Facia Combinations:

Fig A: Bumpers Only "Flush Mount" (B)

Fig B: Wall Setback (S+B)


Fig C: Leveler Cantilever (C+B)

Fig D: Wall Setback AND Leveler Cantilever (S + C + B)



DRIVEWAY GRADE INFORMATION

Level Decline Grade % _____ Incline Grade% _____



TRUCK/TRAILER INFORMATION

Width: Min _____ Max _____
 Height: Min _____ Max _____
 Length: Min _____ Max _____

Hydraulic Tailgate: No Yes Size _____
 Rear Step Section: No Yes Size _____
 Yard Jockeys: No Yes

GS SERIES OPTIONS

Color: Black (standard) Blue* Brown* Green* *Only Available in 22 oz & 40 oz

Head Frame & Side Pad Backers: Wood (standard) Galvanized Steel Channel

Base Material: MAX-1000™ MAX-60™ 40 oz Vinyl 22 oz Vinyl

40 oz NOVALON™** 16 oz NOVALON™**

*NOVALON™ is the equivalent replacement for HYPALON®, a trade name used by DuPont.

Head Curtain Drop: 30" 36" 42" 48" 54" Custom: _____ IN. Hood-Style Head Curtain

Other Options: None Full-Length Guide Stripes Pull Rope Split Head Curtain/Velcro®



WARNING: Cancer and Reproductive Harm-www.P65Warnings.ca.gov