NOVA NHS HYDRAULIC DOCK LEVELER

COMPETITIVE PRODUCT COMPARISON

FEATURES AND BENEFITS

- Capacities range from 25,000 to 100,000-pounds
- Easy push-button activation
- Fully hydraulic deck and lip
- · Velocity fuse stops free-fall situations within 3-inches
- Subframe design allows easy pit cleaning
- · Provides full float at all positions
- Four-way high tensile A572 steel
- Diamond safety tread plate
- 50,000 PSI minimum yield
- · Lip is fully yieldable if impacted
- Working range is 12-inches above/below dock
- Lip keepers for cross-traffic support and added security
- Includes telescoping toe guards
- Full-width rear hinge
- 5-year warranty

MORE EFFICIENT HYDRAULICS: Dual port cylinders allow the hydraulic fluid to travel in both directions, creating a faster lift while costing less to operate and utilizing a smaller pump, motor and tank.

DOCK LEVELER	NOVA
NOVA NHS	✓ YES
Competitor 1	x NO
Competitor 2	x NO
Competitor 3	x NO


REINFORCED DESIGN: Unlike our competitors who use flat stock and light-duty materials, NOVA uses a 4-inch structural C-channel and a full-width rear hinge mounted in compression with a 1-inch diameter steel rod.







GREATEST CAPACITY: The NHS Hydraulic Dock Leveler is available in capacities ranging from 25,000 to 100,000-pounds.



LARGEST SIZE RANGE: Nine size options available to accommodate most applications.

RESTRAINT	NOVA	COMPETITOR		
		1	2	3
6' x 6'	X	Χ	Χ	Χ
6' x 8'	X	Χ	Χ	Х
6' x 10'	X		Χ	
6′6″ x 6′	Χ	Х		Х
6′6″ x 8′	Х	Χ		Χ
6′6″ x 10′	X			
7′ x 6′	X	Х	Χ	Х
7' x 8'	X	Х	Χ	Х
7' x 10'	X		Χ	