




NOVA NMS MECHANICAL DOCK LEVELER

ARCHITECTURAL DRAWING




SELECT	MODEL #	SIZE	"A" PIT WIDTH	"B" LEVELER WIDTH	"C" PIT LENGTH	"D" PIT DEPTH REAR	"E" PIT DEPTH FRONT
	NMS-6006	6'W X 6'L	74"	72"	63"	19 1/2"	20"
	NMS-6008	6'W X 8'L	74"	72"	87"	19 1/2"	20"
	NMS-6010	6'W X 10'L	74"	72"	111"	23 1/2"	24"
	NMS-6606	6'6"W X 6'L	80"	78"	63"	19 1/2"	20"
	NMS-6608	6'6"W X 8'L	80"	78"	87"	19 1/2"	20"
	NMS-6610	6'6"W X 10'L	80"	78"	111"	23 1/2"	24"
	NMS-7006	7'W X 6'L	85"	83"	63"	19 1/2"	20"
	NMS-7008	7'W X 8'L	85"	83"	87"	19 1/2"	20"
	NMS-7010	7'W X 10'L	85"	83"	111"	23 1/2"	24"

SELECT CAPACITY
☐ 25,000LB (CIR) ☐ 30,000LB (CIR) ☐ 35,000LB (CIR) ☐ 40,000LB (CIR) ☐ 45,000LB (CIR) ☐ 55,000LB (CIR)



DWG COMPLETION DATE 1/8/2022		
DESCRIPTION	NMS 25 - 55 DOCK LEVELER	
PART NO.	NMS 25 - 55 DOCK LEVELER	
MATERIAL		
MADE FROM	SHEET 1 OF 2	SCALE 1:28

NOVA NMS MECHANICAL DOCK LEVELER



- | | | |
|--------------------------|-------------------------------|-------------------------------|
| 1 — LIP | 7 — RATCHET BAR | 13 — LIP HOLD GAS CYLINDER |
| 2 — LIP MAINTENANCE PROP | 8 — HOLDOWN | 14 — LIFT ARM ASSEMBLY |
| 3 — PLATFORM | 9 — PLATFORM MAINTENANCE PROP | 15 — LIFT (MAIN) SPRING |
| 4 — LIP LINK | 10 — MAIN BASE FRAME | 16 — PROP PIN AND CLIP |
| 5 — LIP ASSIST SPRING | 11 — SAFETY LEG ASSEMBLY | 17 — WORKING RANGE TOE GUARDS |
| 6 — RATCHET PAWL | 12 — LIP (SNUBBER) SPRING | |


STANDARD FEATURES

- ☒ Multi-position structural steel safety legs
- ☒ Below dock end loading control
- ☒ Extended range float/holdown mechanism
- ☒ Multi-spring counterbalance with single-point adjustment
- ☒ 16-inch yieldable lip
- ☒ Working range toe guards
- ☒ Lip hold gas cylinder
- ☒ Night locks, cross-traffic support
- ☒ Grease fittings
- ☒ Steel channel deck support members (25,000, 30,000, 35,000 and 40,000-pound units)
- ☒ Structural steel support members (45,000 and 55,000-pound units)
- ☒ Three-wheel fork truck protection (45,000 and 55,000-pound units)
- ☒ Two 4-inch 1014 laminated bumpers
- ☒ Easy clean frame design

OPTIONAL FEATURES

- ☐ Rubber weather seal
- ☐ Brush weather seal
- ☐ Optional bumper sizes and types available
- ☐ Three-wheel support (25,000 to 40,000-pound units)
- ☐ Full range toe guards
- ☐ 18-inch lip
- ☐ 20-inch lip
- ☐ 24-inch riser kit (24-inch pit depth is standard on all 10-foot long levelers)
- ☐ Wash down
- ☐ 2-inch foam insulation
- ☐ Spray metalized
- ☐ Cut down leveler length and width
- ☐ Stainless steel pins and lip rods
- ☐ Steel pan: 4-sided
- ☐ Quick pit: 3-sided
- ☐ Three-wheel support



 **WARNING:** Cancer and Reproductive Harm-www.P65Warnings.ca.gov