

SAFE I STAND

With its broad, stable platform and ergonomic design, the safeTstand is engineered to shoulder the weight and stresses of on/off loading in heavy-duty loading dock environments.

Easy-to-deploy with a self-leveling gas-shock system and large all-terrain wheels, our safeTstands instantly create a stronger, safer loading environment. Both models lock with a security pin, but the NSTS-Pro integrates an easier and more ergonomically friendly lever system for faster usage.

FEATURES AND BENEFITS:

- Up to 100,000 lbs Static Load Capacity (45,359 kg)
- Large weight distributing base (17" x 18 1/2") (432 x 470 mm)
- Large, reinforced contact pad (5" x 30" x 1/4") (127 x 762 x 6 mm)
- 16" (406 mm) diameter solid rubber tires for easy handling on any surface (NSTS-Pro)
- 10" (254 mm) diameter wheels (NSTS)
- Easy to position
- Gas shock, self-leveling system with lever locking mechanism (NSTS-Pro)
- Gas shock, self-leveling system with security pin (NSTS)
- 1-year limited warranty
- 38" (965 mm) to 48" (1219 mm) Working Range (NSTS)
- 42-1/2" (1079 mm) to 52-1/2" (1334mm) Working Range (NSTS-Pro)
- Labor to Deploy: Medium (NSTS-Pro)
- Labor to Deploy: High (NSTS)



NSTS-Pro



NSTS



ERGONOMIC & EASY TO OPERATE



PREVENT TRAILER UP-ENDING



PREVENT LANDING GEAR COLLAPSE



WARNING: Cancer and Reproductive Harm-www.P65Warnings.ca.gov